



# EVENT SHOWER W3 WITH SIDE NOZZLES

## FUNCTION DESCRIPTION

The Event Shower W3 is ideal for a Kneipp cooling effect from the legs in direction of the heart by side nozzles. After the start of the programme by a button, the light in the shower changes from white to blue. The lowest pair of side nozzles (level of the legs) starts to spray cold water.

## SCOPE OF DELIVERY OF A COMPLETE PACKAGE

### CONTROL PANEL



Control panel incl. listed parts, pre-tubed, pre-wired and pre-mounted on PP board grey - Part no. 12376:

- Supply with pre-filter and ball valve MS 3/4" female thread
- 3 x Outlet with solenoid valve 1/2" and screwing 1/2"
- Microprocessor controller EDS1 in housing

### TECHNICAL DATA

Electrical supply	230 V-AC, 50 Hz
Power supply	100 W
Water supply	3/4" female thread
Dimensions (W/H/D)	500 x 500 x 200 mm
Weight	app. 7 kg

After an adjustable time the middle pair of nozzles (level of the hips) follows and after the same time the upper pair of nozzles (level of the upper part of the body). The pairs of nozzles can work together or separately from each other. After the end of the programme, the illumination changes back to white and the nozzles are switching off.

### PUSH BUTTON

Details see page 72



- 1 x Push-button plate 1-fold Alu-Dibond - Part no. 19011
- 1 x Bonnet 1-fold - Part no. 21030-1
- 1 x Name plate "Kneipp" - Part no. 17787

### NOZZLES

Details see page 74

- 6 x Side Nozzle - Part no. 19769-2



### ILLUMINATION

- 3 x LED Spots RGB - Part no. 21625
- 3 x Mounting sleeve for LED Spots - Part no. 20973
- 2 x 2,5 m Extension cable - Part no. 20748
- 1 x Controller for LED Spot - Part no. 24630
- 1 x Relais board NT34 for light - Part no. 24926

### TO BE PROVIDED BY THE BUILDER

- Plants room for the installation of the control panel
- Power supply
- Water connection cold 3/4"
- Needed pressure: 3 bar dynamic
- Water quantity: app. 36 l/min at the use of 6 Side Nozzles
- Tubing to the nozzles