

SHOWER VISION –  
WATER IN A NEW DIMENSION



SHOWER VISION LIFTS  
THE SENSUAL EXPERIENCE  
INTO A NEW DIMENSION



# SHOW ERDIME NSIONS



**IMMERSE INTO THE FANTASTIC  
WORLD OF SHOWER VISION**  
Scan the QR-code oder search  
for "WDT Shower Vision" on youtube

## SHOWER VISION – VIDEO SYSTEM FOR EXPERIENCE SHOWERS

Smell, sight, hearing and touch: Experience Showers activate all the users' senses. Aromatised rain showers with light- and sound effects create the most pleasant dream worlds for the user.

ShowerVision lifts this sensual shower experience into another dimension. With the activation of a certain programme, a complementary video sequence starts simultaneously. During the Tropical Rain for example big, smooth water drops patter onto the guest in the shower. A fruity, lively aroma fills the air and the light in the shower changes from white to red. Additionally a video sequence, which gives the user the feeling to relax on a tropical beach starts on a screen.

The core of ShowerVision is a 75" Full-HD-monitor that is integrated in a waterproof bonnet and covered / sealed by a glass door. Different video sequences are pre-programmed.

ShowerVision is designed as a unique attraction for the luxury hotel and spa segment, as well as exclusive private homes.

## POSSIBLE PROGRAMME CONFIGURATION

### Stand-by

The shower is illuminated white and the sequence at the monitor gives the user the feeling to enjoy a sunset at the sea.

### Tropical Rain with aroma

After the start of the programme by a button, the light in the shower changes from white to red. A warm Tropical Rain with big, smooth drops patters onto the guest in the shower. A fruity, lively aroma fills the air. In a distance, you hear the sound of waves and sea. The visual effect of the ShowerVision gives the user the feeling to relax at a tropical beach. After the lapse of the programme, the illumination changes back to white and the sunset at the sea appears on the monitor again.

### Fog Shower

After the activation of the programme, the light in the shower changes from white to blue. A cold, refreshing fog with very fine droplets starts to spray. An alpine creek, which patters calmly over cold rocks, appears at the monitor out of nowhere. At the end of the programme, the illumination changes to white and the user returns to the sunset at the sea.

### Waterfall

The programme starts with a pleasant green illumination and two warm waterfalls that massage the body. The sequence at the monitor gives the user the feeling to stand under a roaring waterfall. After the lapse of the programme, the Stand-by mode is activated again.





# SHOWERVISION SYSTEM CARIBBEAN STORM SED2

## SCOPE OF DELIVERY OF A COMPLETE PACKAGE

### SHOWERVISION

Part no. 27444

- Aluminium installation housing, edged and welded, adapter for the monitor holder and glass panel, sealing flange for the in wall installation and four connections for active ventilation D 80 mm
- Glass panel, ESG safety glass 8 mm, on one side coated frame 125 mm, glued on aluminium support frame
- Heavy duty hinges and spring locks
- Telescopic slide-out for monitor
- LCD 75" Ultra-High Definition Large Format Display
- 4K Multimediaplayer, I/O Player

### CONTROL PANEL

Part no. 14105

- 2 x Supply with pre-filter and ball valve MS 3/4" female thread
- Thermomixer JRG 3/4" with non-return valves
- 2 x Outlet with solenoid valve 1/2" and screwing 1/2"
- 1 x Outlet with solenoid valve 3/4" and screwing 3/4"
- Emptying for the tube to the aromatised nozzle
- Fragrance pump with fragrance reservoir and empty switch
- Dosing valve for the injection of aroma into the water tube
- Non-return according to DIN EN 1717
- Microprocessor controller EDS1 in housing
- Pre-tubed, pre-wired and pre-mounted on PP board grey

### TECHNICAL DATA CONTROL PANEL

Electrical supply	230 V-AC, 50 Hz
Power supply	100 W
Water supply	2 x 3/4" female thread
Dimensions (W/H/D)	750 x 750 x 200 mm
Weight	app. 15 kg

### PUSH BUTTON

Details see page 72

- 1 x Push-button plate 3-fold stainless steel polished - Part no. 25940
- 1 x Bonnet 3-fold - Part no. 21031-1

### CEILING ELEMENT INCL. ILLUMINATION

Details see page 76

- 1 x Ceiling element stainless steel chrome optic (Rain Shower, Waterfall Full Blade, Waterfall Part Blade, Mist - 4 LED RGB Spots) - Part no. 24651

### SOUND

Details see page 80

- 1 x Sound module MP3 - Part no. 18824-1
- 2 x Speaker - Part no. 28536

### TO BE PROVIDED BY THE BUILDER

- Plants room for the installation of the control panel
- Stable recess in the wall
- Equalisation material (building boards) for the realisation of a flush installation with the final surface layer
- Connection to the central ventilation system
- Air exchange rate app. 25 m<sup>3</sup>/h
- Power supply 230 V
- Water connection cold 3/4"
- Water connection warm 3/4"
- Needed pressure: 3 bar dynamic
- Water quantity: app. 70 l/min
- Drain in the plants room
- Tubing to the nozzles

### ACCESSORIES / OPTIONS

- Fragrance
- Air fans

### TECHNICAL DATA TV-SYSTEM

#### Monitor

Dimensions (W/H/D)	959 x 1681 x 71 mm
Visible screen size (W/H)	927 x 1649 mm
Display size	75"
Resolution	2160 x 3840 px
Horizontal frequency	31,5 - 91,1 kHz
Vertical frequency	24,0 - 85,0 Hz (digital signal input)
Power supply	240 V, 50 - 60 Hz
Weight	app. 55 kg
Power consumption	195 W
Speaker output	External loudspeaker socket 15 W + 15 W (8 Ohm)
Operation environment	0 to +40 °C, 20 - 80 % (without condensation)
Operating time	24/7

#### Multimediaplayer

Dimensions (W/H/D)	159 x 144 x 22 mm
Weight	app. 375 g
Power supply internal	12 V-DC, Transformer 240 V, 50 - 60 Hz
Power consumption	18 W
Storage medium	Micro SD Card

#### Media formats

Video Codecs for 4K content:  
H.265/H.264,  
Video Containers for 4K  
H.265/H.264 content:  
.ts, .mov, .mp4  
Video Codecs for Full HD:  
H.265, H.264 (MPEG-4,  
Part 10), MPEG-2, MPEG-1  
Video Containers for Full HD:  
.ts, .mpg, .vob, .mov, .mp4,  
.m2ts  
Images: BMP, JPEG, PNG

Connecting Display 4K HDMI cable



#### Glass panel:

Dimensions (W/H)	1140 x 1880 mm
Material thickness	8 mm
Weight	app. 45 kg
Visible area (W/H)	880 x 1630 mm

#### Installation housing:

Dimensions (W/H/D)	1266 x 2006 x 215 mm
Material thickness	3 mm
Weight	app. 40 kg
Ventilation connections	selectable, 4 x D 80 mm