

ATLANTIC OCEAN RA1 WITH **CEILING ELEMENT STAINLESS STEEL**

FUNCTION DESCRIPTION

Programme 1: Fog Shower with aroma

After the start of the programme by a button, the light in the shower changes from white to blue. A cold, refreshing Fog with very fine droplets starts to spray and a minty, cooling aroma fills the air. You hear the roll of thunder. After the end of the programme, the illumination changes back to white, the Fog and the sound are switching off.

Programme 2: Atlantic Ocean

The programme starts with a warm Waterfall Part Blade. The illumination in the shower changes to a red-green-blue colour change. In a distance you hear the sound of waves and sea. After an adjustable time an additional Fog cools the temperature down. A minty, refreshing aroma fills the air. In the last step of the programme a warm Tropical Rain replaces the cold Fog.

Programme 3: Tropical Rain with aroma

After the start of the programme by a button, the light in the shower changes from white to red. A warm Tropical Rain with big, smooth drops patters onto the guest in the shower. You hear birds tweeting and a fruity, lively aroma fills the air. After the end of the programme, the illumination changes back to white, the Tropical Rain and the sound are switching off.

Programme 4: Caribbean Rain

After the start of the programme by a button, a warm Waterfall Full Blade starts to spray. The illumination in the shower changes to a red-green colour change. You hear the burbling sound of an alpine creek. After an adjustable time a warm Tropical Rain with big, smooth drops increases the water volume. A fruity, lively aroma fills the air. Then the rain gets weaker again and the programme lapses with the warm Waterfall Full Blade. After the end of the programme the illumination changes back to white.

SCOPE OF DELIVERY OF A COMPLETE PACKAGE

CONTROL PANEL



Control panel incl. listed parts, pre-tubed, pre-wired and pre-mounted on PP board grey - Part no. 16639:

- female thread
- Thermomixer JRG 3/4" with non-return valves
- 5 x Outlet with solenoid valve ½" and screwing ½"
- Emptying for the tube to the aromatised rain nozzle
- 2 x Fragrance pump with fragrance reservoir and empty switch
- 2 x Dosing valve for the injection of aroma into the water tube
- 2 x Microprocessor controller EDS1 in housing

TECHNICAL DATA

Electrical supply	230 V-AC, 50 Hz
Power supply	150 W
Water supply	$2 \times \frac{3}{4}$ " female thread
Dimensions (W/H/D)	1000 x 750 x 200 mm
Weight	app. 20 kg

PUSH BUTTON

Details see page 72



- 1 x Push-button plate 4-fold stainless steel polished - Part no. 25941
- 1 x Bonnet 4-fold Part no. 21032-1

CEILING ELEMENT **INCL. ILLUMINATION**

Details see page 76



1 x Ceiling element stainless steel chrome optic (Rain Shower, Waterfall Full Blade, Waterfall Part Blade, Mist - 4 LED RGB Spots) - Part no. 24651

SOUND

Details see page 80



- 1 x Sound module MP3 Part no. 18824-1
- 1 x Speaker Part no. 14366-4

TO BE PROVIDED BY THE BUILDER

- Plants room for the installation of the control panel
- Power supply
- Water connection cold 3/4"
- Water connection warm 3/4"
- Needed pressure: 3 bar dynamic
- Water quantity: app. 50 l/min
- Drain in the plants room
- Tubing to the nozzles
- 2 x Non-return according to DIN EN 1717

ACCESSORIES / OPTIONS

• Fragrance