



POLAR FLASH SED5 WITH CEILING ELEMENT PVC

FUNCTION DESCRIPTION

Programme 1: Fog Shower with aroma

After the start of the programme by a button, the light in the shower changes from white to a blue-green colour change. A cold, refreshing Fog with very fine droplets starts to spray and a minty, cooling aroma fills the air. In a distance you hear the sound of waves and sea. After the end of the programme, the illumination changes back to white, the Fog and the sound are switching off.

Programme 2: Side Nozzles

After the start of the programme by a button, the light in the shower changes from white to green. Cold Side Nozzles massage the guest in the shower. You hear the burbling sound of an alpine creek. After the end of the programme, the illumination changes back to white, the Side Nozzles and the sound are switching off.

Programme 3: Cold Rain

After the start of the programme by a button, the light in the shower changes from white to blue. A cold Drizzle refreshes the guest in the shower. You hear birds tweeting. After the end of the programme, the illumination changes back to white, the Drizzle Rain, the Side Nozzles and the sound are switching off.

Programme 4: Polar Rain

The programme starts with the cold Side Nozzles and green light. You hear the burbling sound of an alpine creek. In the following the cold, refreshing Fog with very fine droplets works together with the Side Nozzles. A minty, cooling aroma fills the air. The illumination changes to a blue-green colour change. In the final programme step the cold Drizzle is working together with the cold Side Nozzles. After the end of the programme the illumination changes back to white, the Drizzle Rain, the Side Nozzles and the sound are switching off.

SCOPE OF DELIVERY OF A COMPLETE PACKAGE

CONTROL PANEL



Control panel incl. listed parts, pre-tubed, pre-wired and pre-mounted on PP board grey - Part no. 14122:

- 1 x Supply cold with pre-filter and ball valve MS 3/4" female thread
- 2 x Outlet with solenoid valve 1/2" and screwing 1/2"
- 1 x Outlet with solenoid valve 3/4" and screwing 3/4"
- Emptying for the tube to the aromatised nozzle
- Fragrance pump with fragrance reservoir and empty switch
- Dosing valve for the injection of aroma into the water tube
- Non-return according to DIN EN 1717
- Microprocessor controller EDS1 in housing

TECHNICAL DATA

Electrical supply	230 V-AC, 50 Hz
Power supply	100 W
Water supply	1 x 3/4" female thread
Dimensions (W/H/D)	750 x 750 x 200 mm
Weight	app. 12 kg

PUSH BUTTON

Details see page 72



- 1 x Push-button plate 4-fold Alu-Dibond - Part no. 19014
- 1 x Bonnet 4-fold - Part no. 21032-1
- 1 x Name plate "Cool Fog" - Part no. 17534
- 1 x Name plate "Side Nozzles" - Part no. 18986
- 1 x Name plate "Cold Rain" - Part no. 19036
- 1 x Name plate "Polar Rain" - Part No. 18597

CEILING ELEMENT INCL. ILLUMINATION

Details see page 76




1 x Ceiling element PVC white Ø 800 x 19 mm with 3 LED Spots RGB Ø 48 incl. RGB controller SAU and 7 m cable with 4 connections for 4 nozzles - Part no. 21768-3

NOZZLES

Details see page 74

- 2 x Drizzle Nozzle 1/2" - Part no. 13527
- 2 x Cover Screen for Drizzle Nozzle - Part no. 13878
- 2 x Fog Nozzle 1/2" - Part no. 13526
- 2 x Cover Screen for Fog Nozzle - Part no. 13877
- 6 x Side Nozzle - Part no. 19769-2



SOUND

Details see page 80



- 1 x Sound module MP3 - Part no. 18824-1
- 1 x Speaker - Part no. 14366-4

TO BE PROVIDED BY THE BUILDER

- Plants room for the installation of the control panel
- Power supply
- Water connection cold 3/4"
- Needed pressure: 3 bar dynamic
- Water quantity: app. 70 l/min at the use of 2 Drizzle-, 2 Fog- and 6 Side Nozzles
- Drain in the plants room
- Tubing to the nozzles

ACCESSORIES / OPTIONS

- Optionally you can use Corian® or backlit ceiling element instead of PVC
- Fragrance