



## 27640 DUFTDOS AK1-NT35-R

### FUNCTION DESCRIPTION

Unit for the aromatisation of Tepidariums, Caldariums, Infrared cabins. With intensity control for cabinets of 50° C and 50 m<sup>3</sup> volume depending on the air exchange rate. Installation in the plants room. Control setting via a five-line display with three sensor buttons.

A small compressor blows air over the surface of a fragrance concentrate that is filled into a little bottle. The fragrance concentrate evaporates and is transported with the air into the room by a tube 6 x 1 and inlet nozzle. The fragrance intensity is adjusted via the software with dosing and pause time. Optionally the DUFT-DOS-AK1-NT35-R can be controlled by a push button from the steam room or by a non-volt contact.

### SCOPE OF DELIVERY

- Microprocessor controller NT35-R
- Compressor 7006 AC
- Bottle adapter
- PET-bottle 250 ml
- Filter star 60 x 8 for the increase of the surface
- Housing with all components installed
- Injection nozzle for cabinets and 5 m dosing tube PE 6 x 1



### TECHNICAL DATA

Electrical supply	230 V/AC 50 Hz
Power supply	app. 60 W
Evaporation performance	app. 5 ml fragrance in 24 h (depending on the intensity of the fragrance and room size)
Measures (B/H/D)	210 x 320 x 120 mm
Weight	app. 2,75 kg
Acoustic emission	app. 55 dBA

### TO BE PROVIDED BY THE BUILDER

- Power socket 230 VAC

### ACCESSORIES / OPTIONS

- Fragrances
- Filter star
- Aroma bottle
- Push button
- Heated nozzle, e. g. for fragrancing snow cabins (only in combination with DUFTDOS-AK1-NT35-R, Part No. 29879)
- System available with two fragrances (Part No. 27641)